

PROJECT:	
MODEL # :	
ITEM # :	QTY :
AVAILABLE W/H :	APPROVAL :

Mega Top Sandwich Prep Tables



BLMT28-HC



BLMT72-HC



BLMT36-HC / BLMT48-HC



BLMT60-HC

STANDARD FEATURES

Cabinet construction

- Stainless steel cabinet construction
Stainless steel interior and exterior (galvanized steel back & bottom).
- Cyclopentane Insulation – Contains no hydro-fluorocarbons (HFCs) and is environmentally friendly
- Drop-in section:
Fans force cold air into this enclosed area keeping stored food items consistently cold
- Insulated pan cover with a stainless steel divider which prevents food spillage into the storage area beneath
- Standard 1/6 / 4" food pans are provided.
Unit accommodates 6" deep pans
- Epoxy coated wire shelves with adjustable shelving height.
- Side rail cutting board bracket with 9 1/2" deep, 1/2" thick cutting board included
- Four (4) 4" diameter swivel casters with front brakes standard.

Refrigeration

- Hydrocarbon refrigerants (R-290) – increases energy efficiency by up to 25% compared to using HFC refrigerants. It is safer for the environment and does not cause ozone depletion.
- Self-contained system, rear mounted compressor.
- Electrodeposition coated evaporator increases performance by maintaining the heat transfer rates over the life of the evaporator and reducing potential corrosion.
- Innovative hot gas frame heating system reduces condensation and increases energy efficiency.
- Refrigerators have a temperature range between 33°F ~ 39°F

Doors

- Self closing doors
- Durable door gasket with easy replacement.
- Lifetime guaranteed heavy duty all metal door handles. (Ni-Cr Plated)

Design

- Self-diagnostic digital temperature control & monitor system
Digital display allows for easy monitoring
Digital controls include automatic evaporator fan motor delay.
- Rounded corner design gives a stylish appearance and reduces chances of injury.
- Visual and audible door open alarm, alarm sounds when doors are not completely closed to protect against food spoilage
- Standard NSF/ANSI Standard 7 compliant

Connection

- 9 ft long flexible three wire cord with molded plug


Optional Features & Accessories

- 2.5" diameter casters available
- 6" adjustable feet available
- Additional shelves are available.
- Drawer models available
- 6" pans available


Mega Top Sandwich Prep Tables

PRODUCT PLAN VIEW

- Top View -



- Front View -



BLMT28-HC


BLMT36-HC

BLMT48-HC


BLMT60-HC

BLMT72-HC


Pan Configuration




BLMT28-HC





BLMT36-HC




BLMT48-HC




BLMT60-HC



BLMT72-HC



- Side View -



PRODUCT SPECIFICATION

Mega Top Sandwich Prep Tables

Model	Product Description			Refrigerant	Temperature Range			Easy Maintenance			Cord Length (ft/m)	
	Mega Top Sandwich Prep Tables			R-290	33°F ~ 39°F			Sliding Condensing Unit			9.8ft (3m)	
	Doors	Capacity (Cu.Ft.)	Shelves	Cabinet Dimensions (inches / mm)			HP	Voltage	Amps	NEMA config.	Weight (lbs / kg)	
L				D	H	Net Weight					Ship Weight	
BLMT28-HC	1	7	1	27 1/2" (699mm)	37 9/32" (947mm)	44 1/4" (1122mm)	1/4+	115V / 60Hz	4.1	NEMA 5-15	161 (73)	203 (92)
BLMT36-HC	2	9.5	2	36 3/8" (923mm)	37 9/32" (947mm)	44 1/4" (1122mm)	1/4+	115V / 60Hz	4.1	NEMA 5-15	190 (86)	234 (106)
BLMT48-HC	2	13.1	2	48 3/8" (1227mm)	37 9/32" (947mm)	44 1/4" (1122mm)	1/4+	115V / 60Hz	4.7	NEMA 5-15	227 (103)	289 (131)
BLMT60-HC	2	16.7	2	60 3/8" (1533mm)	37 9/32" (947mm)	44 1/4" (1122mm)	1/4+	115V / 60Hz	4.9	NEMA 5-15	276 (125)	340 (154)
BLMT72-HC	3	20.2	3	72 3/8" (1839mm)	37 9/32" (947mm)	44 1/4" (1122mm)	1/4+	115V / 60Hz	5.4	NEMA 5-15	311 (141)	390 (177)

*BLUE AIR has the right to change specifications without further notice.