



AX-513RHD

Half Size Convection Oven with Humidity Digital controls - Reversing Fan - 3 shelves









Digital controls	Time, temperature, humidity, 3 coo-
	king cycles for each program, automa-
	tic pre-heating
Load capacity	3 shelves for half size sheet pans
High speed reversing fan	1 (3200 rpm)
Space between shelves	3" (75 mm)
Power requirements	1,650 Watts / 120 V / 60 / 1
	Oven supplied with power cord
	and plug
Temperature	86° - 500° F
Equipped with	16 hour timer - Signal at end of cycle
Cavity size(inches)	18.7" x 15" x 9.6" (WxDxH)
Unit dimensions (inches)	22.05" x 25.48" x 17.90" (WxDxH)
Shipping dimensions (inches)	23.63" x 26.77" x 19.69" (WxDxH)
Net / Ship weight	62 lb / 73 lb

Features

- Advanced airflow design
- Automatic high speed reversing fans
- Digital programmable controls / 99 programs / automatic pre-heating / 3 cooking cycles for each program
- Interior halogen light
- Includes electro valve for direct water connection
- Micro safety switch shuts oven off when door is open
- Heavy duty stainless steel body construction
- "Cold Door" design with double pane glass
- Reinforced door hinges
- Oven door can support weight limit of 80 lbs.
- Oven cavity is insulated with ultra-high temperature fiberglass insulation
- 3 Stainless steel wire shelves
- Ovens can be stacked (kit required)
- Warranty: 2 years parts & 1 year labor exclusive of lights, gaskets and glass

OVEN STANDS & PROOFERS



AX-501 OVEN STAND SHIP WT: 43 lbs

- HD stand with tray slides for half size sheet pans
- Dimensions: 23.30" x 20.87" x 31.50"
- Accommodates any "5" series ovens



AX-PR5 SHIP WT: 133 lbs



- Capacity: 8 half size sheet pans
- Space between pans: 3"
- 208-240/60/1, 2000 Watts
- Heat setting up to 140°F
- Manual fill water supply in bottom tray

CONVECTION ACCESSORIES



DEFLECTOR CODE: **124-DEF**

- 1 is required for "5" series
- Air deflector plate for delicate baking



STACKING KIT "5" SERIES CODE: 124-KIT5

- Stacking kit for "5" Series

LINE DRAWINGS

AX-513RHD





