

# 1767-SK

## **Low Temperature Smoker Oven**



ecosmart • Halo Heat . . . a controlled, uniform heat source that maintains close temperature tolerances throughout the cooking and holding function. Offers uniform and consistent cooking on a daily basis, low shrinkage of bulk or portion-cut protein items, higher food moisture content, and significantly longer holding life.

- Smokes with real wood chips no pressure cooking, no artificial smoke flavor.
- Smoke timer offers a choice of mild, medium, or heavy smoke flavor.
- Cooks, smokes, and holds meats, poultry, and fish.
- Cold smokes fish and cheese.
- Induces natural enzyme action in meat for tenderizing.
- Less energy usage than conventional ovens.
- Reduces labor and evens-out work loads.
- Non-magnetic stainless steel interior, racks, and shelves resist corrosion.
- Simple control senses temperature drops faster, providing quick heat recovery time.

#### **Short Form Spec**

Alto-Shaam double compartment 1767-SK Smoker oven is constructed with a stainless steel exterior. Oven includes stainless steel doors with magnetic latch. Each compartment interior includes two (2) completely removable, non-magnetic stainless steel side racks with eleven (11) pan positions spaced on 1-3/8" (35mm) centers, two (2) stainless steel wire shelves, one (1) stainless steel rib rack, a removable stainless steel drip pan with drain and a wood chip container. Oven is furnished with an exterior, front mounted stainless steel drip tray and one (1) sample bag each of cherry, hickory, apple and maple wood chips. Oven includes one (1) set of 5" (127mm) casters -2 rigid, and 2 swivel with brake.

Each compartment has a simple control with an On/Off power switch; cook temperature knob, 200°F to 325°F (94°C to 160°C); hold temperature knob, 60°F to 205°F (16°C to 96°C); digital display, up/down arrows to set cook and hold time; and a sixty minute smoking timer. Control features indicator lights for the cook, hold, and smoke functions, and when the oven is calling for heat. Oven is equipped with a voltage conversion switch, located on the back of the oven, for voltage selection (208 or 240 V.A.C.) at time of installation.

☐ **Model 1767-SK:** Double compartment low temperature smoker oven with simple control.

ANSI/NSF 4









### **Factory-Installed Options**


- · Door Choices: ☐ Solid Door, standard ☐ Window Door, optional
- Door Swing Choices:
- ☐ Right-hand swing, standard ☐ Left-hand swing, optional
- · Voltage Choices:
- □ 208-240V
- □ 230V
- Exterior Panel Color Choices:
- ☐ Stainless steel, standard ☐ Burgundy, optional
- ☐ Custom color, optional
- · Cooking thermostat limit set at 250°F for restricted areas of the U.S.A.
- ☐ Specify on order as required
- ☐ Extended drip tray (not available with bumper)

#### **Additional Features**

#### ☐ Rib Rack Shelf • Item SH-2743

Special non-magnetic stainless steel wire shelf designed to hold ribs or fish in an upright position for more even smoking. Each shelf will hold thirteen full ribs. One (1) rib rack shelf is furnished with each compartment. Additional racks are available as an option.

Capacity: Two (2) rib rack shelves per compartment.






On all Cook & Hold heating elements (EXCLUDES LABOR).




W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. Phone: 262.251.3800 800.558.8744 U.S.A./CANADA Fax: 262.251.7067 800.329.8744 U.S.A. only www.alto-shaam.com



# **Low Temperature Smoker Oven**





 $^*60\text{-}11/16"$  (1540mm) - with optional 3-1/2" (89mm) casters  $^*62\text{-}1/8"$  (1577mm) - with optional 6" (152mm) legs

<b>Dimensions:</b> H	I x W x D		
Exterior:			
	61-15/16" x 27-1/16" x 32-3/4"		
	(1572mm x 686mm x 832mm)		
Interior: (each compartment)			
	20-1/16" x 21-15/16" x 26-1/2"		
	(510mm x 531mm x 673mm)		

Electrical							
V	Ph	Hz	A	kW			
208	1	60	31.0	6.4	No cord		
240	1	60	25.0	6.0	or plug		
230	1	50/60	24.3	5.6	No cord or plug		

Product/Pan Capacity					
100 lb (45 kg) maximum per compartment					
Volume maximum: 53 quarts (67 liters)					
	Full-Size Pans	Gastronorm 1/1			
	Per Compartment:	Per Compartment:			
Nine (9)	20" x 12" x 2-1/2" (530mm x 325mm x 65mm)				
Five (5)	20" x 12" x 4" (530mm x 325mm x 100mm)				
Full-size sheet pans per compartment:					
Up to Five (5)*	18" x 26" x 1" on wire shelves only				
*additional shelves required					

Clearance Requirements				
Rear	3" (76mm) from non-heated surfaces 18" (457mm) from heat producing equipment			
Тор	2" (51mm)			
Left, Right	1" (25mm)			
Weight				
<b>Net:</b> 356 lb (161 kg) <b>Ship:</b> 450 lb (204 kg)				
Carton dimensions: (L X W X H)				
35" X 35" X 82" (889mm x 889mm x 2083mm)				

	Installation Requirements
	— Oven must be installed level.
	The oven must not be installed in any area where it may be affected by steam, grease, dripping water, extreme
	temperatures, or any other severely adverse conditions.
	<ul> <li>Appliances with casters and no cord or plug must be secured to the building structure with a flexible connector.</li> </ul>
_	Not factory supplied.
	Smoker ventilation requirements to be determined by local installation codes.

Accessories						
☐ Bumper, Full Perimeter	5010371	☐ Pan (	☐ Pan Grid, Wire, 16-3/8" x 24-3/8" (416mm x 619r			
☐ Carving Holder, Prime Rib	HL-2635	— fits	— fits inside of an 18" x 26" sheet pan			
Carving froncer, frime his	11L-2033	□ Secur	rity Panel w/ Ke	5013938		
☐ Carving Holder, Steamship (Cafeteria) Round	4459	☐ Shelf, Stainless Steel, Flat Wire		SH-2324		
Casters, Stem - 2 rigid, 2 swivel w/brake		☐ Shelf, Stainless Steel, Rib Rack			SH-2743	
□ 3-1/2" (89mm)	5008017	Woodchips, bag				
□ Door Lock with Key - each handle	LK-22567		2.0 lb (.9 kg)	1.25 cu. ft. (35 L)	2.5 cu. ft. (71 L)	
*		Cherry	☐ WC-22540	☐ WC-22541	□ WC-37746	
☐ Drip Pan with Drain, 1-11/16" (43mm) deep	14831	Apple	□ WC-22542	□ WC-22543	□ WC-37747	
☐ Drip Pan without Drain, 1-5/8" (41mm) deep	1014684	I <del>I </del>				
		Maple	☐ WC-22544	☐ WC-22545	☐ WC-37748	
☐ Legs, 6" (152mm), Flanged (set of four)	5011149	Hickory	□ WC-2828	□ WC-2829	□ WC-37749	



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. Phone: 262.251.3800 800.558.8744 U.S.A./Canada Fax: 262.251.7067 800.329.8744 U.S.A. only www.alto-shaam.com